

Galvanized Base—Standard Roof Flashing





Specifications:

Furnish and install roof vent flashing with 25 mil. aluminum base, fitted with elastomer collar. Unit shall be Water-Tite item number checked below as manufactured by IPS Corporation, as per corresponding dimen-sional characteristics, or equivalent. (Do not use Petroleum based mastics, sealing compounds, or paints on collar portion of all flashings, on all hardbase, flexible, or rain collars.)

Product Code	Model	Vent Size	Dim. W	Dim. L	Dim. R	Dim. F	Dim. C	Dim. H
81900	AB1	1-1/4" - 1-1/2"	8-3/4"	12-1/2"	3-1/2"	2-3/8"	4-1/4"	2-1/4"
81905	AB2	2"	8-3/4"	12-1/2"	3-1/2"	2-3/8"	4-1/4"	2-1/4"
81910	AB3	3"	10-3/4"	14-1/2"	2-5/8"	2-3/8"	5-1/2"	2"
81915	AB4	4"	12"	16"	3-3/4"	2-3/4"	6-1/2"	2-1/8"
81916	AB5	1/2", 3/4", 1"	8-3/4"	12-1/2"	3-1/2"	2-3/8"	4-1/4"	2-5/8"

500 Distribution Parkway, Collierville, TN 38017 = Phone: 800-888-8312 = Fax: 901-853-5008 = www.ipsroofingproducts.com